

# Hybrid PRO

Simplicity Through Innovation




Follow us @ HIKVISION Oceania



# What is Hybrid PRO?

HIKVISION®




## Professional Hybrid System

Delivering **high speed, stable and reliable** intrusion alarm solution



# System Topology

HIKVISION®



# Wired Control Panel



**8** on-board zones and **56** wired/wireless zones expandable;  
**4** on-board outputs and **60** wired/wireless outputs expandable



## Onboard LAN & Wi-Fi

Optional PSTN, 3/4G communication module



**4-ch** IPC video verification,  
**8** wired PIRCAM, HD GIF verification



**1 Speed-X** BUS communication technology



Battery type: **12V 7Ah**, Lead acid battery  
(Battery is not included by default)



Compatible with AX PRO **Wireless Detectors**  
through wireless receiver



# Simple Installation

HIKVISION®



PCB is fixed by buckles, without any extra screw.  
Easier and faster for assembly and disassembly.



Internal Use Only

# Speed-X BUS Technology

## Higher speed transmission

The transmission speed could reach up to **500kb/s** via Speed-X communication protocol, which is **150 times** of the traditional technology.

## Wired PIRCAM supported

Able to connect **Wired PIRCAM** for **HD image verification**, helps user or ARC verify the authenticity of alert more effectively and efficiently.

## Longer transmission distance

The transmission distance of Speed-X BUS technology could reach up to **900m**, and the modules could also be connected in cascade mode to extend the distance to **5,400m**

HIKVISION



**HIKVISION<sup>®</sup>**

# Compatible with AX PRO Wireless Peripherals

The AX PRO series wireless detectors can also connect to Hybrid PRO panel via wireless receiver


















Wireless Detector



Wired Detector





# Peripheral: Wireless Inputs

				
DS-PDP15P-EG2-WB Internal PIR Detector	DS-PDD12P-EG2-WB Dual-Tech Detector	DS-PDC15-EG2-WB PIR Curtain Detector	DS-PDPG12P-EG2-WB PIR-BG Sensor	DS-PDMCS-EG2-WB Slim Magnetic Contact
				
DS-PDMC-EG2-WB Magnetic Contact	DS-PDBG8-EG2-WB Glass Break Sensor	DS-PDMCK-EG2-WB Magnet Shock Sensor	DS-PDWL-E-WB Water leak sensor	DS-PDCL12-EG2-WB Ceiling 360 PIR
				
DS-PDEB1-EG2-WB Emergency button (Single button)	DS-PDEB2-EG2-WB Emergency button (Dual buttons)	DS-PDEBP1-EG2-WB Portable Emergency Button (single button)	DS-PDEBP1-EG2-WB Portable Emergency Button (Dual buttons)	DS-PDTPH-E-WB Temperature & Humidity Detector

# Peripheral: Wireless Outputs

			
DS-PS1-E-WB External Sounder	DS-PS1-I-WB Internal Sounder	DS-PM1-O1L-WB Relay Module (0~36VDC, 5A)	DS-PM1-O1L-WB Relay Module (90~240VAC, 13A)

# Peripheral: Wireless Remote Controls


	
DS-PK1-E-WB Keyfob	DS-PT-M1 Tag

# Multiple Communication Options

4 ARCs supported



With **36 hours** of long battery life



**LAN, WIFI, GPRS, 3/4G, PSTN**  
Multiple communication method




# IVaaS——Video Verification



## Option 1

Live HD Video via Hik-Connect



## Option 2

Onboard Video Clips for Verification



Intrusion Verification  
as a Service Now Available

Verify alarms with real-time high-quality video clips

# Wired PIRCAM

(Infrared Version)



## Volumetric Coverage

Detection Range: **12m / 85.9°**



## 24/7 Verification

Infrared Light for dark night



## Pet-Immunity

Could filter the false alarm triggered by animals (**≤ 30 KG**).



## Creep-Zone Protection

Support Creep-Zone Protection.



## Speed-X BUS Technology

The transmission distance of RS485 can be **900m** at the speed of **500kb/s**.




## Higher Image Resolution

Support JPEG image capture with resolution of **2MP**.




## GIF Verification

Up to **20 pictures** fused to a GIF.




# Wired LCD Keypad

Support display SI name & contact info



- LCD screen display
- Front button cover for better protection
- Faster operational response due to **Speed-X BUS technology**
- Built in Tag reader & AX PRO keyfob supported
- Support 3EOL (Alarm, tamper alarm, anti-masking)
- Supports **2 on-board inputs** and **1 relay output**



	Operation	Keypad Simple Mode	Keypad Standard Mode with "Arm with Faults" on
Arm :	Away Arm	Op1:PWD +  ; Op2:Tag	PWD / Tag +  +  (Fault check)
	Stay Arm	Op1:PWD +  ; Op2:Tag (Hold 3s)	PWD / Tag +  +  (Fault check)
	Area Away Arm	PWD + # + Area +	PWD / Tag + # + Area +  +  (Fault check)
	Area Stay Arm	PWD + # + Area +	PWD / Tag + # + Area +  +  (Fault check)
Disarm:	Disarm	Op1:PWD +  ; Op2:Tag	PWD / Tag +
	Area Disarm	PWD + # + Area +	PWD / Tag + # + Area +
	Silence Alarm	PWD +  (Hold 3s)	PWD / Tag +  (Hold 3s)
	Duress	Duress Code +	Duress Code +
Relay:	Enable Relay	PWD +	PWD / Tag +
	Note	Press  + # for selection and press  to confirm	
Configuration: Enter Configuration admin/installer PWD +			


## 4 indicators :

- Power: Green
- Faults: Fault-Orange / Find me mode-flashing green
- Armed: Blue
- Alarm: Red

## 1 backlight:

- Keypad button backlight: White

# Wireless receiver



- Speed-X BUS technology with the speed of **500 kb/s**
- Compatible with **AX PRO wireless detectors**
- Supports 32 wireless detectors, 4 wireless indoor sounders and 8 wireless outdoor sounders
- LED display to show status
- Plastic case
- LED indicator: Green: power/find me 2. Orange: alarm/fault




**Wireless Detector**

# Zone Input Expander



- Speed-X BUS technology with the speed of **500 kb/s**
- **Long transmission distance in cascade mode**
- Support cascade connection typology
- **Support 8 onboard zones, 3EOL**
- 1 AUX power supply
- LED display to show status


**The Cascade Wiring Mode**



■■■■ Up to 7 expanders




# Zone Output Expander



- Speed-X BUS technology with the speed of **500 kb/s**
- **Long transmission distance in cascade mode**
- Support cascade connection typology
- **4 relays onboard (High & Low Voltage)**
- LED display to show status

**The Cascade Wiring Mode**



■ ■ ■ ■ Up to 7 expanders

# AX Hybrid PRO Family

HIKVISION®




Control Panel




LCD Keypad



Hik-ProConnect



Hik-Connect



Input Expander



Wired PIRCAM



Wired Detector



Outdoor Tri-tech  
Outdoor Curtain



AX PRO  
Wireless Detector



Wireless Receiver



Output Expander



Wired Sounder



Wireless Sounder



Relay Module  
(0~36VDC, 5A & 90~240VAC, 13A)


# System Management

HIKVISION®



**Hik-Connect**  
for end-user

Intuitive interface with one-key operation



**Hik-ProConnect**  
for installer

Device health monitoring via APP/Portal

# Self-Monitoring via Hik-Connect

Connect easily wherever you are!



One tap to arm & disarm system



Check 7s video clips or live videos




Check system & device status



Receive instant alarm notification



Admin account can add users to manage same system




Hik-Connect



Alarm call




SMS



# Monitored by ARC



LAN/WIFI  
/GPRS/3G/4G



- SIA/CID
- IP Receiver PRO

# 3<sup>rd</sup> Party ARC Platform

HIKVISION®

Option 1: Integrating via SIA-DC09.

AX Hybrid PRO Hub could be integrated into 3<sup>rd</sup> party ARC software directly via SIA-DC09 protocol.




The standard **Plug & Play Protocol**, suitable for some traditional Residential and SMB ARCs that only need alarm notification.



# 3<sup>rd</sup> Party ARC Platform

HIKVISION<sup>®</sup>

## Option 2: Integrating via HIK IP Receiver Pro.



It provides super-fast and easy-to-use connection via **IP Receiver Pro**, with no additional integration, cost and also no need for port forwarding.

Other Hikvision Systems

Hik-Connect

End User